








INLINE FILTERED SUPPLY UNIT



ANCILLARY EQUIPMENT

 <p>Vibration Isolators Ref. I-1</p>	 <p>FT - Mounting Foot Ref. J-6</p>	 <p>Controllers & Sensors Ref M-20, M-23/24</p>
 <p>Variable speed drives Ref. M-8-13</p>	 <p>SD - Star/Delta Switch Ref. M-7</p>	 <p>RV - Alfa Relief Vent Ref. D-10</p>

DESCRIPTION

The Inline Filtered Supply Unit has been designed to provide filtered outside air to a range of applications where direct fresh air intake is not possible or practical.

Typical Applications

Filtered supply air into areas such as switch rooms, data rooms, commercial kitchens, shopping centres, factories and warehouses.

Features

- Robust, yet lightweight galvanised steel construction
- Mixed-flow impeller with high performance blade geometry
- Pure-V washable G4 filters on the fan discharge side that can be easily accessed via a removable side panel
- Choice of external rotor motors available in single phase and 3-phase configurations
- Supplied with TDF flanges as standard for inline mounting or installed with an external grille for flush to wall mounting

Construction

Galvanised steel housing with material filters on the discharge side of the fan.

Industry standard 35mm TDF profile flange for easy connection to ducting.

Motors

Type – external rotor squirrel cage induction motor

Electricity supply - 230V, single-phase and 415, 3 phase, 50Hz

Bearings – sealed-for-life, ball

3-phase motors can be speed controlled using variable speed drives

Testing

Air flow tests based on ISO 5801.

Noise tests based on ISO 13347-3.

Performances shown are based on clean filters.

As air flow will be affected by room pressurisation, care should be taken to ensure adequate air relief is provided.

Internal thermal Protection

Auto-reset type fitted as standard

Special Notes

Pure-V filters

The Inline Filtered Supply Unit incorporates Airepure Pure-V filters that are pleated for extra durability and will hold their shape without the need of a wire support metal cage. Pure-V panel filters are washable.

The filters should be checked during cleaning for wear or damage and replaced when necessary. They can be removed via the side access panel on the discharge side of the fan.

Airepure Pure-V filters are tested with an efficiency of G4 to standard EN 779:2002.

Differential Pressure Switch

A differential pressure switch can be used to provide indication that the filter needs maintenance.

SUGGESTED SPECIFICATION


The Inline series of Filtered Supply Units shall be designed and manufactured by Fantech Pty Ltd and be of the model numbers shown on the schedule/ drawings.

The unit will have a galvanised steel housing with 35mm TDF profile flange connections and incorporate a weatherproof external grille if mounted flush to an external building wall. It will include Pure-V washable G4 filters on the discharge side of the fan.

The unit shall incorporate a Mixed-Flow impeller made from high performance injected moulded composite plastic and driven by an external rotor motor as nominated.

All performance data shall be for a complete assembled unit, and based on ISO 5801 for air flow and ISO 13347-3 for noise.

HOW TO ORDER



INLINE FILTERED SUPPLY UNIT

TECHNICAL DATA

Model FSD... FSE..	Nom. Speed, rev/ sec	Max Operating Temp (°C)		dB(A) @ 3m	FSE...ER 1 ph.		FSD...ER 3 ph.		In-Duct Sound Power Levels, Lw dB re 1pW							
					kW	Amps	kW	Amps	63	125	250	500	1k	2k	4k	8k
314	23	60	Inlet	46	0.22	1.10	0.21	0.50	74	70	64	62	60	60	59	53
			Outlet	50					74	71	64	65	64	66	61	56
316	15	60	Inlet	36	0.09	0.48	0.09	0.26	61	60	54	52	50	50	49	43
			Outlet	40					64	61	54	55	54	56	51	46
354	23	60	Inlet	42	0.37	1.85	0.33	0.68	65	68	61	58	54	56	55	49
			Outlet	46					66	67	61	60	62	60	58	52
356	16	60	Inlet	33	0.12	0.56	0.13	0.36	56	59	52	49	45	47	46	40
			Outlet	37					57	58	52	51	53	51	49	43
404	22	60	Inlet	49	0.58	2.60	0.54	1.20	69	73	66	66	60	63	62	56
			Outlet	52					71	71	66	67	68	67	64	58
406	15	60	Inlet	40	0.28	1.35	0.22	0.56	60	64	57	57	51	54	53	47
			Outlet	43					62	62	57	58	59	58	55	49
454	23	60	Inlet	51	1.10	5.20	1.00	1.95	73	75	70	67	64	65	63	58
			Outlet	55					78	74	72	71	71	68	65	59
456	15	60	Inlet	40	0.37	1.75	0.32	0.70	62	64	59	56	53	54	52	47
			Outlet	44					67	63	61	60	60	57	54	48
458	9	60	Inlet	28	-	-	0.19	0.39	50	52	47	44	41	42	40	35
			Outlet	32	55	51			49	48	48	45	42	36		
504	21	60	Inlet	56	1.65	7.40	1.45	2.80	77	81	76	71	70	69	66	61
			Outlet	59					85	81	82	73	76	72	67	60
506	14	60	Inlet	48	0.54	2.50	0.48	0.88	69	73	68	63	62	61	58	53
			Outlet	51					77	73	74	65	68	64	59	52
508	11	60	Inlet	40	-	-	0.31	0.50	61	65	60	55	54	53	50	45
			Outlet	43	69	65			66	57	60	56	51	44		
564	22	45	Inlet	57	-	-	2.50	4.60	79	81	77	72	71	71	69	64
			Outlet	63	82	84			80	79	78	77	75	69		
566	15	60	Inlet	49	0.84	4.20	0.86	2.20	73	73	69	64	63	64	59	52
			Outlet	54					75	76	71	70	70	69	64	57
568	13	60	Inlet	45	-	-	0.62	1.10	69	73	67	61	59	57	53	46
			Outlet	50	72	73			68	67	66	63	58	50		
636	15	60	Inlet	51	-	-	1.35	3.40	65	73	69	67	66	65	61	57
			Outlet	56	68	76			72	74	72	70	66	58		
638	12	60	Inlet	45	-	-	0.86	1.85	65	67	65	61	61	59	55	49
			Outlet	51	69	71			68	70	67	64	59	50		

* Electrical data in **bold** type refers to fans that are fitted with 2-speed star/delta motors as standard.